OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION 27 TOWNSHIP DATE: 2-22-06 16 RANGE \_ 5 PARTY CHIEF: Wilcoxen CREV: TYPE OF MARKER: Harrison fd METHOD OF ESTABLISHMENT: County: 10-30-00 erman IN. S.P.C. E ZONE NAD '83. 16052702 506682.4410(m) NAME: N: E 74680.7100(m) 1. E. 30th St. 3000 N

30th St. 3000 N

Original post set 1820 by John Hendricks with witness: 10" beech S 37 E 18 linnks; 8" dogwood N 31 W 5 links per Marion County Atlas pg. 15. Survey by 0.W. Voorhis 4-14-1863 indicates no stone or witness få per Warren Township Legal Survey Book pg. 38. MCSO 10-19-49 called a stone 6" down. Monroe 10-5-51 called a stone 6" down. Monroe 4-11-57 called a stone 4" down. MCSO 4-22-75 called a railroad spike. Wilcoxen 5-5-76 called a railroad spike. Wilcoxen 8-31-77 called a bolt spike. MCSO 1-23-79 called a brass plug. Gries 11-30-87 called brass plug. Whiteside 9-18-96 called PK anil. Kiste 10-3-97 called a brass plug. Excavated by Wilcoxen 10-27-00 and railroad spike fd 6" down. No other stone or monuments were fd. Harrison set. Re-tied 2-22-06 by Wilcoxen.

16052702		
REF.	DISTANCE	DESCRIPTION
1.	36.99	Cut 'x' S edge of telephone manhole
2.	41.29	Cut 'x' in center of sewer manhole
3.	43.14	Mag nail w/bw W PwP#16-451F 18"up
4.	39.48'	Top nut of fire hydrant
5.	76.90'	SW corner of brick column fence line
		→ · · · · · · · · · · · · · · · · · · ·
	1.8	